

### Cost-effective product for slim light box...




















### **Features**

- Nichia LED with Vf=6V, high-power 1W, 3030 package
- Aluminum PCB adopted, for better heat diffusion
- Good Back light source with high brightness and uniform light
- Reversed polarity connect protection, no damage to bar if positive and negative connection reversed
- Adopt WOGO 2060 connector or AMPR connector(Female/male), more convenient for installation
- Constant current IC: Ensure the stability of the product performance and less brightness decay

### **Application**

Sign light Box 5-10CM



# Cost-effective product for slim light box

## **Specifications**

Code Name	YD7 3.0 -0303	YD7 3.0 -0506	YD7 3.0 -1012	
Color		White		
сст(к)	6500-7000			
View Angle(°)	160			
Luminous Flux(lm)	357	708	1375	
RA	80			
Light Efficiency(lm/w)	96.4	94.4	91.7	
Voltage	24V DC			
Current(MA)	155	310	620	
Power(W/pcs)	3. 7	7. 5	15	
Standard Serial connection Qty (pcs)	8	4	2	
Operating Temperature(°C)	-25~+60			
Storage Temperature(°C)	-25~+70			
Protection Class	IP 60			


### Color Available






## Cost-effective product for slim light box

### **Dimension**



### Luminous Intensity Distribution Diagram

YD7 3.0 -1012=960[37.80]




#### BLUEVIEW ELEC-OPTIC TECH CO.,LTD

Tel: +86-28-8148 0011 Fax: +86-28-8148 1258
Mail: sales@blueviewled.com Web.: www.blueviewled.com
Add: No.1000, Section 2, 2nd Konggang Road, Southwest
Aviation Industrial Development Zone, Chengdu, Sichuan, China.
Zip code: 610207



## Cost-effective product for slim light box

## Installation //



#### Installation scheme for reference

#### ① 3mm Thickness Acrylic

Thickness	Bar to Bar Distance	Qty/m²	Illumination
4cm	9cm	12pcs	7710-10800lux
5cm	11cm	10pcs	5870-8720lux
7cm	15cm	7pcs	4620-5890lux
10cm	15cm	7pcs	4280-5630lux
12cm	17cm	6pcs	2950-5130lux


### ② Lightbox Blank Fabric (no picture)

Thickness	Bar to Bar Distance	Qty/m²	Illumination
4cm	8cm	13pcs	6620-8370lux
5cm	9cm	12pcs	4750-7290ux
7cm	15cm	7pcs	2980-4360ux
10cm	17cm	6pcs	2980-4360lux
12cm	17cm	6pcs	2320-3480ux




## Cost-effective product for slim light box

### **Package**





Put the products into the carton and seperated the layer by foam ,then seal it with sealing tape ,stick the laber at the side of the carton



#### Notice:

1. Carton size: outside carton with five layers of cardboard. Specification as below:

Part No.	Product size	Carton size (mm)	Qty per carton	Net weight (NW/kg)	Gross weight (GW/kg)
YD7 3.0 -0303	240*20	550*400*340	500	17.16(1±10%)KG	18.56(1±10%)KG
YD7 3.0 -0506	480*20	550*400*340	380	19.5(1±10%)KG	20.9 (1±10%)KG
YD7 3.0 -1012	960*20	1030*210*240	180	18.7(1±10%)KG	20.1 (1±10%)KG

- 2. This product packed by transparent PE bag, two pieces in one bag.
- 3. Above mentioned quantity and weight are based on above packing method only, quantity and weight differs when applying other packing, please refer to actual situation.

#### BLUEVIEW ELEC-OPTIC TECH CO.,LTD